



## Lumidigm® V-Series Fingerprint Modules

*The V-Series provides biometric authentication for over two billion banking transactions per year around the world.*

### Key Enhancements:

- Up to four times faster image capture (V300)
- Top-rated MINEX III certified algorithm
- FBI-certified WSQ compression
- New SDK tools

### Use Cases:

- **Physical access control** and time & attendance terminals
- **Banking** — ATMs, teller stations, logical access
- **Healthcare** — medical dispensing, E-prescribing (EPCS), record access, benefit verification, patient tracking
- **Citizen ID** — Benefit distribution (pensions, healthcare, welfare), voter verification, national ID.

## INDUSTRY-LEADING BIOMETRIC AUTHENTICATION

- **Best Available Biometric Performance** — From wet to dry, dirty to bright, patented multispectral imaging technology is perfect for every-day, deployment conditions.
- **Delivers Seamless User Experience** — Fast and intuitive, the V-Series provides reliable authentication for any user demographic.
- **Detects Fraudulent Verification Attempts** — Award-winning liveness detection rejects fakes and spoofs while ensuring access to authorized individuals.
- **Meets Application Requirements** — Superior biometric performance combined with excellent interoperability and easy integration makes the V-Series the first choice for demanding deployments.
- **Provides a Low Cost of Ownership** — Robust and field-proven, V-Series modules require minimal maintenance, even in unattended and high-throughput applications.

Lumidigm V-Series Fingerprint Modules use patented multispectral imaging technology to deliver unmatched ability to acquire, excellent biometric interoperability, best-in-class liveness detection and proven robustness for low total cost of ownership in embedded or streaming fingerprint authentication applications.

The firmware supplied with embedded V-Series modules (V300) now provides **four times faster image capture**, a top-ranked MINEX III certified algorithm for better accuracy, and FBI-certified WSQ image compression for fast and accurate image transfers. Streaming V-Series modules (V310) include the MINEX III algorithm and FBI-certified WSQ image compression features when running Lumidigm SDK 6.0 or higher on a USB host device.

The V-Series provides superior images for anyone, anytime, in any environment for superior biometric performance in the real world. Multispectral imaging technology simultaneously reads the surface and subsurface fingerprint to capture clear

images every time — even when finger surface features are hard to distinguish due to age, dirt, finger pressure, and skin or environmental conditions.

With best-in-class liveness detection, the V-Series provides a quick and easy user experience while reducing the opportunity for unauthorized access.

The V-Series modules are durable and easy to integrate into a variety of finished products, including ATMs, physical access control terminals, medical dispensing devices and others, using USB or RS-232 interfaces. Designed for demanding user authentication applications, the V-Series conforms to biometric interoperability standards including ANSI and ISO fingerprint minutia template standards, a top-ranked MINEX III certified algorithm and FBI-certified WSQ finger image compression.

The configurable V-Series supports image, template and match score outputs in embedded or streaming operating modes with updated development tools using Lumidigm SDK 6.0.

## Lumidigm® V-Series Module key features:

- Multispectral imaging with liveness detection
- Four times faster capture than earlier V30x versions
- MINEX III minutia algorithm supports ANSI/ISO standards
- IP65 protection at the platen for harsh environments

## Available in two operating modes:

- Embedded modules (V300) process biometric data on the device, including template extraction and matching, speeding time to market.
- Streaming modules (V310) connect to a USB host to process biometric data using the Lumidigm SDK.

## SPECIFICATIONS

	V300-40 (Embedded)	V300-xx (Embedded legacy)	V310-00 (Streaming)
<b>FINGERPRINT IMAGING SYSTEM</b>			
<b>Technology</b>	Patented Lumidigm optical multispectral imaging		
<b>Image resolution / bit depth</b>	500 dpi / 8-bit, 256 grayscale		
<b>Platen area</b>	0.7" x 1.1" (18mm x 28mm) ellipse		
<b>BIOMETRIC FUNCTION OUTPUTS</b>			
<b>Image output format</b>	ANSI 381, ISO 19794-4, WSQ compression (FBI certified)	ANSI 381, WSQ compression	ANSI 381, ISO 19794-4, WSQ compression (FBI certified)
<b>Template output format</b>	1:1: ANSI 378, ISO 19794-2 1:N: ANSI 378+	ANSI 378	1:1: ANSI 378, ISO 19794-2 1:N: ANSI 378+ (SDK 6+); Proprietary (SDK 5)
<b>Verify (1:1) template match score</b>	ANSI 378 or ISO 19794-2	ANSI 378	ANSI 378 or ISO 19794-2 (SDK 6+)
<b>Identify (1:N) score</b>	Supported on USB host with SDK 6+	ANSI 378	ANSI 378+ (SDK 6+), ANSI 378 (SDK 5)
<b>Latent and liveness detection</b>	Yes. (Field-updatable algorithm)		
<b>FINGERPRINT TEMPLATES</b>			
<b>Verify (1:1) template storage</b>	Not supported on device	Up to 1,000	Limited by USB host memory
<b>Identify (1:N) template storage</b>	Not supported on device (can output 1:N template)	Up to 400 users (V300-30 only)	Up to 5,000 users (SDK 6+); Up to 1,000 users/group (SDK 5)
<b>BIOMETRIC PROCESSING TIMES</b>			
<b>Finger touch to image capture</b>	200 ms (typical)	800 ms (typical)	800 ms (typical)
<b>Finger touch to image out</b>	800 ms (typical)	1.3 sec (typical)	800 ms - 1 sec (typical)
<b>Finger touch to 1:1 score/template</b>	1.5 sec (typical)	2.0 sec (typical)	900 ms - 1.1 sec (typical)
<b>Finger touch to 1:N score</b>	Not supported on device	2.1 sec (typical, V300-30 only)	950 ms - 1.1 sec (typical)
<b>Liveness detection (when enabled)</b>	500 ms V30x-40 and V30x-30, 100 ms on prior versions (typical)		50 ms (typical)
<b>ENVIRONMENTAL RANGE</b>			
<b>Ingress protection</b>	IP65 dust and water protection at platen		
<b>Temperature (operating)</b>	Enclosure: -10 to 60°C / No Enclosure: 0 to 60°C		
<b>Humidity (operating)</b>	Enclosure: 0-100% RH condensing / No Enclosure: 0-95% RH condensing		
<b>ESD immunity (operating)</b>	IEC 61000-4-2 Level 4+/-15 kV Air		
<b>INTERFACE MODULE</b>			
<b>Device interface</b>	USB 1.1 or 2.0 (480 Mbps), RS-232 (115.2 kbps)		USB 2.0 (480 Mbps)
<b>Memory, platform requirement</b>	n/a		64 MB RAM, Intel 32b/64b platform
<b>Operating systems supported</b>	Windows 10/8/7 (32b/64b), Windows XP, Linux, Android (V300)		
<b>Encryption</b>	n/a		Encrypted video for playback protection
<b>FORM FACTOR</b>			
<b>Overall dimensions</b>	2.68"W x 2.61"D x 2.02"H (68 mm x 66 mm x 51 mm)		
<b>Housing</b>	Polycarbonate plastic, glass fiber reinforced; platen area is IP65		
<b>POWER SUPPLY REQUIREMENTS</b>			
<b>Supply current — operational</b>	+5 VDC 460 mA (peak)		+5 VDC 300 mA (peak)
<b>Supply current — idle</b>	+5 VDC 200 mA (typical)		+5 VDC 100 mA (typical)
<b>STANDARDS COMPLIANCE</b>			
<b>Interoperability</b>	ANSI 378, ISO 19794-2:2011, ANSI 381, ISO 19794-4:2011, MINEX III, NFIQ	ANSI 378, ISO 19794-2:2005, ANSI 381, ISO 19794-4:2005, MINEX 2004, NFIQ	ANSI 378, ISO 19794-2:2011, ANSI 381, ISO 19794-4:2011, MINEX III, NFIQ (SDK 6+)
<b>Device certifications</b>	CE, FCC Part 15 Class B, EN 60950, IEC 62471, RoHS, DEA EPCS, support for thin clients		CE, FCC Part 15 Class B, EN 60950, IEC 62471, RoHS, DEA EPCS, WHQL

North America: +1 512 776 9000  
Toll Free: +1 800 237 7769  
Europe, Middle East, Africa:  
+44 1440 714 850  
Asia Pacific: +852 3160 9800  
Latin America: +52 55 9171 1108

For more information, please [click here](#).

© 2021 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and Lumidigm are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2021-01-15-lumidigm-v-series-modules-ds-en

PLT-02168