

# IN Tag™



## ROBUST LOW, HIGH AND ULTRAHIGH FREQUENCY RFID TAGS THAT PERFORM IN TOUGH CONDITIONS

- **Durable** – built to withstand the rigors of industrial processing, transportation and outdoor use
- **Versatile** – mounts anywhere without compromising performance: glass, plastic, or wood, with options for on metal mounting
- **Diverse selection** – broad spectrum of available frequencies, memory sizes and diameters with multiple fixation methods

IN Tag™ passive contactless RFID transponders are highly water, chemical and shock resistant, ATEX certified for use in explosive environments, withstand peak temperatures up to 285° F (140° C) and are UL94-HB flame resistant.

Low frequency (LF) IN Tag discs perform well affixed to virtually any surface. They offer reliable, cost-effective tagging for near-proximity reader applications, with data storage from a 64-bit user ID, up to 2048-bit read-write capability.

High frequency (HF/NFC) discs offer anti-collision technology for faster data processing, larger memory storage, and improved read ranges. HF IN Tag devices are available with up to 1 kbit EEPROM or 8 kilobyte FRAM - the highest memory specified by ISO/IEC 15693. FRAM tags are radiation resistant to survive Gamma sterilization and offer an exceptional speed with up to 10 billion write cycles.

Ultrahigh frequency (RAIN® UHF) IN Tag RFID tags can be read from up to 9.8 ft (3 m). Entire pallets of individual containers or equipment may be identified and item level status updated, as articles roll through distribution and receiving points. They are compliant to EPC Global Class 1 Gen 2 standards and readers.

HID IN Tag RFID tags come in a variety of sizes. For LF and HF applications, tiny 0.79 in (20 mm) discs may be glued or embedded virtually anywhere. If a larger read range is required, HID offers 1.18 in (30 mm) and 1.97 in (50 mm) options, which include pre-drilled holes for screw attachment. UHF tags come in 1.97 in (50 mm) and 2.17 in (55 mm) discs.

HID IN Tag transponders are an excellent performance-level tag. For lighter-duty applications, consider HID Epoxy Disc or World Tag™ transponders.

**TECHNOLOGY HIGHLIGHTS:**

- Low Frequency (125 kHz), up to 2048 bit read-write memory
- High frequency (13.56 MHz), up to 8 kilobyte read-write memory
- Ultrahigh frequency (865 to 928 MHz), 240 bit EPC, 640 bit read-write memory
- Food compatible
- Flame and UV resistant
- Disc diameters of 20, 30, 50 mm (55 mm with spacer)
- Optional configurations for mounting on metal

For more information, contact [tagsales@hidglobal.com](mailto:tagsales@hidglobal.com)



# IN Tag™



HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.



II 1G Ex ia IIC T4 Ga  
I M1 Ex ia I Ma

For more information,  
contact [tagsales@hidglobal.com](mailto:tagsales@hidglobal.com)

## SPECIFICATIONS











IN Tag™						
Low Frequency - LF						
	200	300		500		
<b>Base Model Number</b>	601182	623183	624183	601183	624185	601185
<b>ELECTRONIC</b>						
<b>Operating Frequency</b>	125 kHz					
<b>Chip Type</b>	Unique	HITAG S		Unique	HITAG S	Unique
<b>Memory</b>	64 bit read-only	256 bit EEPROM	2048 bit EEPROM	64 bit read-only	2048 bit EEPROM	64 bit read-only
<b>Anti-collision</b>		Yes			Yes	
<b>Reading Distance</b> 2 W reader ERP, free space	Dependent upon reader, environment and application					
<b>PHYSICAL</b>						
<b>Dimensions</b>	Ø 0.79 x 0.12 in (Ø 20 x 3 mm)	Ø 1.18 x 0.12 in (Ø 30 x 3 mm)		Ø 1.97 x 0.12 in (Ø 50 x 3 mm)		
<b>Mounting Method</b>	Embed, glue	Embed, glue, screw				
<b>Fixation Hole Size</b>		Ø 0.20 in (5.2 ± 0.3 mm)				
<b>Affixes To</b>		Glass, plastic, wood, metal				
<b>Housing Material</b>		PPA Polyphthalamide [ISO 1874: PA6T/6I-GF50]				
<b>Color</b>		Black				
<b>Weight</b>	0.04 oz (1.3 g)	0.11 oz (3 g)		0.34 oz (9.5 g)		
<b>CHEMICAL AND MECHANICAL</b>						
<b>Water</b>	IP68, IP69K, 176° F (80° C), 100 bar, 30 sec. 16 l/min					
<b>Withstands Exposure To</b>	Fuel B, mineral oil, petroleum, salt mist, vegetable oil, [UV resistant ISO 4892-2], [food compatible, directive 02/72/EC], [flame resistant UL94-HB]*					
<b>Environmental Test Conditions</b>	68° F (20° C), 100 h					
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]					
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]					
<b>Drop Test</b>	100 x 5.9 ft (1.8 m)					
<b>Axial / Radial Force</b>	800 N / 500 N, 10 sec.					
<b>THERMAL</b>						
<b>Storage</b>	-40° to +194° F (-40° to +90° C), 1000 h					
<b>Operating</b>	-13° to +185° F (-25° to +85° C)					
<b>Shock/Fatigue</b>	-40° to +194° F (-40° to +90° C) 50x5 min with 30 sec transition					
<b>Peak</b>	284° F (140° C), 100 h					
<b>OTHER</b>						
<b>Standards</b>	EN 60079-0:2009; EN 60079-11:2007; EN 60079-26:2007					
<b>Box Size</b>	1500 pcs	750 pcs		250 pcs		
<b>Options</b>	Custom embossed, printed or no logo					
<b>Warranty</b>	2 Years					

\*Flame Resistance UL94-HB not applicable for spacer of INTag 500 OM or INTag 500 UHF OM.

## INDUSTRY AND LOGISTICS:

- **Asset tracking and logistics**
  - Tool and equipment inventory
  - Maintenance management
- **Automation and manufacturing**
  - Process automation
  - Real-time materials inventory
  - Food processing
- **Returnable transport items**
  - Inventory and distribution tracking
  - Container maintenance
- **Waste management**
  - Bin tracking
  - Recycling compliance monitoring
  - Improved invoicing and service accuracy
  - Route optimization
  - Incentive-based waste and recycling programs

## SPECIFICATIONS

	IN Tag™									
	High Frequency - HF						Ultrahigh Frequency - RAIN UHF			
	200	300 / 300 OM	500	200	300	300 8KB	500 EU	500 EU OM	500 US	500 US OM
										
<b>Base Model Number</b>	629182-012 629182-013 (FOAM)	629183-012 629183-312 (OM)	629185-012 629185-312 (OM)	634182	634183	6D1183-010	6E5185-010	6E5185-310	6E5186-010	6E5186-310
<b>ELECTRONIC</b>										
<b>Operating Frequency</b>	13.56 MHz						865-868 MHz (ETSI)		902-928 MHz (FCC)	
<b>Chip Type</b>	ICODE SLIX 2			F-Mem			G21M			
<b>Memory</b>	ICODE SLIX - 896 Bit User Memory ICODE SLIX2 - 2560 Bit User Memory			2 Kbyte FRAM		8 Kbyte FRAM	640 bit EEPROM (96 bit TID, 256 bit EPC)			
<b>Anti-collision</b>	Yes									
<b>Reading Distance</b> 2 W reader ERP, free space	Dependent upon reader, environment and application						Up to 9.8 ft (3 m)			
<b>PHYSICAL</b>										
<b>Dimensions</b>	Ø 0.79 x 0.12 in (Ø 20 x 3 mm)	Ø 118 x 0.12 in (Ø 30 x 3 mm)	Ø 1.97 x 0.12 in (Ø 50 x 3 mm)	Ø 0.79 x 0.12 in (Ø 20 x 3 mm)	Ø 118 x 0.12 in (Ø 30 x 3 mm)	Ø 1.97 x 0.14 in (Ø 50 x 3 mm)	Ø 217 x 0.51 in (Ø 55 x 13 mm)	Ø 1.97 x 0.14 in (Ø 50 x 3 mm)	Ø 217 x 0.51 in (Ø 55 x 13 mm)	Ø 217 x 0.51 in (Ø 55 x 13 mm)
<b>Mounting Method</b>	Embed, glue	Embed, glue, screw		Embed, glue	Embed, glue, screw					
<b>Fixation Hole Size</b>		Ø 0.20 in (5.2 ± 0.3 mm)				Ø 0.20 in (5.2 ± 0.3 mm)				
<b>Affixes To</b>	Glass, plastic, wood	Glass, plastic, wood, Metal (OM)	Glass, plastic, wood	Glass, plastic, wood		Glass, plastic, wood	Metal, glass, plastic, wood	Glass, plastic, wood	Metal, glass, plastic, wood	
<b>Housing Material</b>	PPA Polyphthalamide [ISO 1874: PA6T/6I-GF50]									
<b>Color</b>	Black									
<b>Weight</b>	0.04 oz (1.3 g)	0.11 oz (3 g)	0.34 oz (9.5 g)	0.04 oz (1.3 g)	0.11 oz (3 g)	0.35 oz (9.5 g)	1.27 oz (36 g)	0.35 oz (9.5 g)	1.27 oz (36 g)	1.27 oz (36 g)
<b>CHEMICAL AND MECHANICAL</b>										
<b>Water</b>	IP68, IP69K, 176° F (80° C), 100 bar, 30 sec. 16 l/min									
<b>Withstands Exposure To</b>	Fuel B, oil, petroleum, salt mist (not applicable for 300 OM), vegetable oil, [UV resistant ISO 4892-2], [food compatible, directive 02/72/EC], [flame resistant UL94-HB]*									
<b>Environmental Test Conditions</b>	68° F (20° C), 100 h									
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]									
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]									
<b>Drop Test</b>	100 x 5.9 ft (1.8 m)									
<b>Axial / Radial Force</b>	800 N / 500 N, 10 sec.									
<b>THERMAL</b>										
<b>Storage</b>	-40° to +194° F (-40° to +90° C), 1000 h									
<b>Operating</b>	-40° to +185° F (-40° to +85° C)			-13° to +185° F (-25° to +85° C)			-40° to +185° F (-40° to +85° C)			
<b>Shock/Fatigue</b>	-40° to +194° F (-40° to +90° C), 50x5 min with 30 sec transition									
<b>Peak</b>	284° F (140° C), 100 h									
<b>OTHER</b>										
<b>Standards</b>	EN 60079-0:2009, EN 60079-11:2007, EN 60079-26:2007, ISO 15693, ISO 18000-3					ISO 18000-6C, EPC C1G2, EN 60079-0:2009, EN 60079-11:2007, EN 60079-26:2007				
<b>Box Size</b>	1500 pcs	750 pcs	250 pcs	1500 pcs	750 pcs	750 pcs	250 pcs	50 pcs	250 pcs	50 pcs
<b>Options</b>	Custom embossed, printed or no logo									
<b>Warranty</b>	2 Years									

North America: +1 512 776 9000 • Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800 • Latin America: +52 55 9171 1108

© 2017-2021 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and IN Tag are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2021-02-11-hid-rfid-ii-in-tag-family-ds-en

PLT-00276

Part of ASSA ABLOY



[hidglobal.com](https://www.hidglobal.com)